Part No. P0911648 03

Business Communications Manager 2.5

Call Detail Recording System Administration Guide

NORTEL NETWORKS™

Copyright © 2001 Nortel Networks

All rights reserved. February 13, 2001.

The information in this document is subject to change without notice. The statements, configurations, technical data, and recommendations in this document are believed to be accurate and reliable, but are presented without express or implied warranty. Users must take full responsibility for their applications of any products specified in this document. The information in this document is proprietary to Nortel Networks NA Inc.

Trademarks

NORTEL NETWORKS is a trademark of Nortel Networks.

Microsoft, MS, MS-DOS, Windows, and Windows NT are registered trademarks of Microsoft Corporation.

All other trademarks and registered trademarks are the property of their respective owners.

Contents

Preface 13

Before you begin 13
Emergency 911 Dialing 13
Text conventions 13
Acronyms 14
Related publications 15

Chapter 1
Introduction 17

About Call Detail Recording 17
Your role as System Administrator 18

Chapter 2
Configuring Call Detail Recording 19

Unified Manager 19
The Call Detail Recording keys 21
The Report Parameters 22
Report formats and types 23
SL-1 reports 23
Norstar reports 23
Report Language 24
Report Filter 24
All calls 24
Outgoing calls only 24
Prefix strings 25
Account Code Feature Code 25
Account Code list 26
Using Account Codes 26
The Report Options 27
Date Format 28
Header Format 28
DNIS Info 28
Connect Char (Characters) 29
Clip File Schedule 29
File size 29
Disk Space limit 29
The Market Parameters 30
CLID with Name 31
Long CLID Support 31

CLID with Call Type 31
Support Call Charge 31
Answer Supervision 31
Call Filter Duration 31
Hospitality Record 31
The Prefix Bin Settings 32
Prefix filter 32
The Access Bin Settings 33
Access Bin Settings 34
Suppress Length Settings 34
Saving configuration changes 34
The Configuration menu 35
Configuration Commit 35
Configuration Undo 36
Configuration Clip File 37
Data File Transfer 39
Features of Data File Transfer 39
Central server requirements 39
Scheduling the transfer of the Call Detail Recording information 39
Transferring the Call Detail Recording information immediately 42

Chapter 3
Call Detail Recording Reports 43

SL-1 reports 43
Report logs 43
SL-1 report types 43
SL-1 report field definitions 44
SL-1 report options 45
SL-1 Standard reports 45
SL-1 CLID reports 46
SL-1 Target line/Physical lines 47
Auto Attendant and Call Center station set numbers 47
Advice of charges at end of call (AOCE) 47
Norstar reports 48
Norstar report types 48
Norstar Standard reports 48
Norstar CLID reports 49
Norstar report field definitions 49
Norstar Real Time report format 51
Norstar All report format 52
Auto Attendant and Call Center station set numbers 53
Standard Hospitality record format 53

Target line/Physical lines 53
Busy reports 54
Direct Inward Dial (DID) busy 54
Target line busy 54
Bearer capability data 54
PRI Call-by-call service 55
Voice over IP calls 56
Dialed number identification service 56
Call connected digit separator 56
External call forward 57
Norstar report field definitions 58
Norstar Standard and CLID report description 60
Printable line descriptions 60
Norstar Real Time record description 64
Real Time Hospitality record format 65
Advice of charges at end of call 65

Chapter 4
Install CDRClient Application 67

Call Detail Recording display 67
The CDRClient window 67
Call Detail Recording Record Security 69
CDR Group User Administration 69
CDR User Management 70
Create a user profile 70
Modify user privileges 70
Delete a user name 71
Call Detail Recording Domain User Management 71
Add a name to a Domain User Group 71
Modify user privileges 72
Delete a user name 72
CDR User Management additional information 72
Glossary 75

Index 77

Figures

Figure 1 The Comprehensive window 20
Figure 2 The Summary window 20
Figure 3 Startup on Reboot window 21
Figure 4 The Report Parameters window 22
Figure 5 The Report Options window 27
Figure 6 The Market Parameters window 30
Figure 7 The Prefix Bin Settings window 32
Figure 8 The Access Bin Settings and Suppress Length Settings window 33
Figure 9 The Configuration reminder window 35
Figure 10 The Commit option window 36
Figure 11 The Undo option window 37
Figure 12 The Clip File option window 38
Figure 13 Sample outgoing call 45
Figure 14 Sample incoming call 45
Figure 15 Sample call transfer 46
Figure 16 Sample conference call 46
Figure 17 Sample incoming call with CLID 46
Figure 18 Sample incoming call with Call Information and without CLID 46
Figure 19 Sample incoming call transferred with Call Information available 46
Figure 20 Sample target line transfer 47
Figure 21 Sample end of call with charges rounded down 47
Figure 22 Sample end of call with charges rounded up 47
Figure 23 Sample end of call with pulse charges 47
Figure 24 Sample end of call with no charge 48
Figure 25 Sample end of call with charges not available 48
Figure 26 Sample outgoing call 48
Figure 27 Sample incoming call 49
Figure 28 Sample incoming call with CLID 50
Figure 29 Sample call with CLID not answered 50
Figure 30 Sample call with truncated CLID 50
Figure 31 Sample call with partial CLID 50
Figure 32 Sample call with DNIS 51
Figure 33 Sample call transfer 52
Figure 34 Sample call with Standard, CLID and Real Time information 52
Figure 35 Sample room status vacant 53
Figure 36 Sample room status basic 53
Figure 37 Sample room status mid 53
Figure 38 Sample room status full 53
Figure 39 Sample target line and physical line 54

Figure 40 Sample busy call with DID 54
Figure 41 Sample busy call on a target line 54
Figure 42 Sample incoming call with Bearer capability 55
Figure 43 Sample PRI 55
Figure 44 Sample incoming call with VoIP 56
Figure 45 Sample incoming call with DNIS 56
Figure 46 Sample call with digit separator 57
Figure 47 Sample external call with external call forward 57
Figure 48 Sample internal call with external call forward 58
Figure 49 Standard and CLID report formats 59
Figure 50 Real Time record format 60
Figure 51 Sample start header line 60
Figure 52 Sample restart line 61
Figure 53 Sample call ringing line 61
Figure 54 Sample outgoing line 61
Figure 55 Sample unanswered call line 61
Figure 56 Sample busy line 61
Figure 57 Sample hold and off hold lines 61
Figure 58 Sample conference start and end lines 61
Figure 59 Sample call transfer line 62
Figure 60 Sample call transfer from line 62
Figure 61 Sample end call line 62
Figure 62 Sample digits dialed line 62
Figure 63 Sample invalid password line 62
Figure 64 Sample account code line 62
Figure 65 Sample password 63
Figure 66 Sample last line 63
Figure 67 Sample physical line 63
Figure 68 Sample CLID information 63
Figure 69 Sample room status 63
Figure 70 Sample external call forward 64
Figure 71 Sample room status vacant 65
Figure 72 Sample room status basic 65
Figure 73 Sample room status mid 65
Figure 74 Sample room status full 65
Figure 75 Sample charges in dollars 66
Figure 76 Sample charges in lira 66
Figure 77 Sample charges in units 66
Figure 78 Sample with no charges 66
Figure 79 Sample charges not available 66
Figure 80 CDRClient window 68
Figure 81 User Administration window 69

Figure 82 Property Sheet window 70
Figure 83 Domain User Group Profile window 72

Tables

Table 1 Summary window parameters 21
Table 2 Report Parameters 22
Table 3 Sample Account Codes 26
Table 4 Report Options parameters 27
Table 5 The Market Parameters window parameters 30
Table 6 Configuration reminder window 35
Table 7 Data File Transfer parameters 40
Table 8 Field definitions for line 1 44
Table 9 Field definitions for line 2 44
Table 10 Report options and letter codes 45
Table 11 Report options and letter codes 51

Preface

Your Business Communications Manager telephone system has many features that you can customize to keep up with changes in your workplace.

This guide provides information about how to program a Business Communications Manager telephone. This information includes items such as programming personal speed dials, transferring a call, and using special features. Some of the features included in the Business Communications Manager telephone system are, conference calls, group listening, group pickup, directed pickup, and call tracking.

This guide is aimed at the day to day operators of the Business Communications Manager telephone system.

Before you begin

Plan the programming changes you want to make before you begin. Record the changes so that you have the information at hand. For example, before you program system speed dial numbers, create a record so that you have all the numbers and codes available.

Programming applies to both North America and International telephones in your Business Communications Manager system.

Emergency 911 Dialing

Emergency 911 Dialing is the capability to access a public emergency response system.

State and local requirements for support of Emergency 911 Dialing service by Customer Premises Equipment vary. Ask your local telecommunications service provider about compliance with applicable laws and regulations.

Emergency 911 Dialing may not apply to International systems.

Text conventions

This guide uses the following text conventions:

`Bold`	Is used to highlight a programming level within the Unified Manager menu. Example: **ALL** report type .
italic text	Indicates new terms and book titles. Example: *Business Communications Manager Installation and Maintenance Guide*.
`Forward slash /`	Separates names where two actions are assigned to one button. Example: `MM/DD/YY` .

Acronyms

This guide uses the following acronyms:

AL	Alarm
AOCE	Advice of charges at end of call
ASM	Analog Station Module
ATA	Analog Terminal Adapter
BRI	Basic rate interface
CDR	Call Detail Recording
CFAC	Call Forward all Calls
CFB	Call Forward Busy
CFNA	Call Forward No Answer
CLASS	Custom Local Area Signalling Service
CLID	Calling Line Identification
CMS	Call Management Services
DID	Direct inward dial
DISA	Direct inward system access
DN	Directory number
DND	Do not disturb
DNIS	Dialed Number Identification Services
DRT	Delayed Ring Transfer
ERC	Express routing code
ETSI	European Telecommunications Standards Institute
HS	Hospitality services
IP	Internet Protocol
ISDN	Integrated Services Digital Network
ISO	International Organization for Standardization
KB	Kilobyte
LAN	Local Area Network
MB	Megabyte
PC	Personal computer
PBX	Private branch exchange
PIN	Personal Identification Number
PRI	Primary Rate Interface

RC	Room condition
RO	Room occupancy
SLR	Selective line redirection
URL	Uniform Resource Locator
WAN	Wide Area Network

Related publications

For more information about using Business Communications Manager 2.5, refer to the following publications:

- *Programming Operations Guide*
  This document provides more information about using Unified Manager.

Chapter 1
Introduction

The Nortel Networks Business Communications Manager Call Detail Recording is an application that records and reports call activity. Each time a telephone call is made to or from your company, you can record the information about the call. When the call is completed, you can print information about the call in a report. Call Detail Recording also provides information on incoming calls as the events occur. This information appears in a Real Time Call record.

About Call Detail Recording

Call Detail Recording provides information about:

- date and time of the call, and digits dialed
- the originating and the terminating line or station set
- whether an incoming call was answered
- elapsed time between origin of a call and when it was answered
- whether a call was transferred or put on hold
- call duration
- call charges
- calls associated with Account codes
- incoming call Calling Line Identification (CLID) information
- Bearer Capability of the line in the call
- Hospitality records for room occupancy status
- Real Time records for ringing, DNIS, answered, unanswered, transferred, and released events for incoming calls with CLID information and Hospitality room occupancy status

Note: Call Detail Recording delivers Custom Local Area Signalling Services (CLASS), Call Management Services (CMS), Automatic Number Identification, and Dialed Number Identification Services (DNIS) in the form of CLID reports. Contact your customer service representative for more information.

You can use information collected by Call Detail Recording to:

- allocate telephone costs to departments or individuals
- charge back telephone costs to billable clients through Account codes
- determine whether the telephone system is being used efficiently
- guard against abuse of the telephone system
- provide immediate call information to database applications through Real Time call records
- track changes in room occupancy status

Your role as System Administrator

As System Administrator, you perform the initial and ongoing administration tasks.Your tasks include:

- administering Call Detail Recording
- determining Account codes used as references for tracking telephone calls
- interpreting reports

Warning: SECURITY ALERT: Call Detail Recording provides information such as the date and time of the call, digits dialed, incoming call information and call time elapsed. This includes sensitive and personal information such as telephone banking numbers, credit card numbers and personal identification numbers. Digits dialed are not maintained as confidential.

As System Administrator it is solely your responsibility to advise the system users that their telephone dialing information can be monitored and recorded.

Further, LAN-based access to call records (passive or real time) demands a greater emphasis on call record security. Limitations and security arrangements can vary depending on the network environment and how the customer administers and limits access to the call records. Consult with the appropriate members of your organization regarding the proper safeguards.

Chapter 2
Configuring Call Detail Recording

Call Detail Recording uses configuration parameters to specify the kinds of calls to be reported as well as the report type and format. Each parameter can be changed at any time.

Unified Manager

1 Open Business Communications Manager Unified Manager.

The Comprehensive window appears. The Business Communications Manager navigation tree shows the following five keys:

- System
- Resources
- Services
- Management
- Diagnostics

Figure 1 shows the Comprehensive window. Refer to "The Comprehensive window" on page 20.

Figure 1 The Comprehensive window



2 On the navigation tree click the **Business Communications Manager** key and then click the **Services** key.

3 Click the **Call Detail Recording** key.
The Summary window appears.

Figure 2 shows the Summary window. Refer to "The Summary window" on page 20.

Figure 2 The Summary window



Table 1 shows the parameters you can configure using the Summary window. Refer to "Summary window parameters" on page 21.

Table 1 Summary window parameters

Name	**Version**
CDR	CDR Software Version
Description	
Business Communications Manager Call Detail Recording	
Status	**Startup on Reboot**
Up	Enable-Automatic
Down	Enable-Manual
	Disable

Figure 3 shows the Startup on Reboot parameters. Refer to "Startup on Reboot window" on page 21.

Figure 3 Startup on Reboot window



The Call Detail Recording keys

From the Services folder, click the **Call Detail Recording** key.
Call Detail Recording shows the following six keys:

- Report Parameters
- Report Options
- Market Parameters
- Prefix Bin Settings
- Access Bin Settings
- Data File Transfer

When you click on a key the window for that item appears.

The Report Parameters

When you select the Report Parameters key from the Comprehensive window, the Report Parameters window shown in Figure 4 appears. Refer to "The Report Parameters window" on page 22.

Figure 4 The Report Parameters window



Table 2 shows the parameters you can configure using the Report Parameters window. Refer to "Report Parameters" on page 22.

Table 2 Report Parameters

Format	**Report Type**
SL-1	SL-1 Standard
Norstar	SL-1 CLID
	Norstar Standard
	Norstar CLID
English	Norstar Real Time
French	Norstar All
Danish	
Swedish	**Report Filter**
Dutch	All
Spanish	Outgoing
German	Prefix
Italian	Account Code
Norwegian	
Feature Code	
F900-999	

Report formats and types

Call Detail Recording generates both Norstar and SL-1 report types. SL-1 offers two report formats: Standard and CLID. Norstar offers four report formats: Standard, CLID, Real Time and All.

Note: The Report format default is SL-1. The Report type default is Standard.

SL-1 reports

Use the SL-1 report format when you are supplying the Call Detail Recording output to legacy commercial call accounting packages or equipment.

This report format supports recording Standard report type as well as the Calling Line Identification (CLID) report type.

The SL-1 CLID report prints the CLID information only if the information is delivered. Otherwise, it records the call in SL-1 Standard report type.

The SL-1 report format does not support the recording of Bearer Capability and DDI Busy reports.

Note: For more information about SL-1 reports, refer to "SL-1 reports" on page 43.

Assign the SL-1 report type

From the Report Parameters window, you can assign the SL-1 report type as Standard or CLID.

To assign or change Report Parameters:

1. Click the **Report Parameters** key.
   The Report Parameters window opens.
2. In the **Format** list box, select **SL-1**.
3. In the **Report Type** list box, select **Standard** or **CLID**.

Note: Call Detail Recording reports only the CLID Information for lines that are capable of delivering CLID. Calls on non-CLID capable lines are reported in SL-1 Standard report format.

Norstar reports

Use the Norstar report format for more detailed and concise call reports.

Note: For more information about Norstar reports, refer to "Norstar reports" on page 48.

Assign the Norstar report type

From the Report Parameters window, you can assign the Norstar report type as Standard, CLID, Real Time or All.

To assign or change Report Parameters:

1. Click the **Report Parameters** key.
   The Report Parameters window opens.
2. In the **Format** list box, select **Norstar**.
3. In the **Report Type** list box, select **Standard**, **CLID**, **Real Time** or **All**.

Report Language

If your Business Communications Manager server supports other languages, select either English or one of the alternate languages. The Report Language default is English.

To assign or change the Report Language:

1. Click the **Report Parameters** key.
   The Report Language window opens.
2. From the **Report Language** list box, select **English** or an alternate language.

Note: The Report Language you select only affects Call Detail Recording reports. The language assigned to each telephone determines the language used in the Account codes.

Report Filter

The Report Filter option allows you to specify the type of calls to be collected. Select one of the following:

- All calls
- Outgoing calls only
- Calls that match the prefix strings on long distance
- Calls with Account codes only

Only one of the above reports can be selected at a time. The Report Filter default is All and can be changed from the Call Detail Recording Report Parameters window.

All calls

Call Detail Recording reports all incoming and outgoing calls.

Outgoing calls only

Call Detail Recording only reports on outgoing calls. Incoming calls are not reported.

Prefix strings

Call Detail Recording reports calls matching the pre-determined long distance digit strings.

The purpose of the Prefix option is to report only long distance calls, calls to certain area codes or calls to specific numbers. If you select the Prefix Report filter, you must also specify the prefix digits.

If the first digits dialed match one or more of the programmable prefix strings, the call is reported, otherwise the call is not reported. You can have a maximum of eight prefix strings assigned at one time. The maximum length for each prefix string is eight digits.

Note: The Prefix filter defaults are 0, 1, 90, 91, 411 and 9411. Invalid Password attempts are reported regardless of the Report Filter selected.

Account Code

Call Detail Recording reports only calls with account codes associated with them.

To assign or change a Report Filter:

1. Click the **Report Parameters** key.
   The Report Parameters window opens.
2. In the **Report Filter** option, select **All**, **Outgoing**, **Prefix** or **Account Code**.
3. Click the **OK** button.

Account Code Feature Code

Account Codes allow you to cross-reference telephone calls from your company to different clients or for telephone activities.

Before Account Codes can be entered by users, a Feature Code must be established. This Feature Code is any number between 900 and 999 and ranges from one to 12 digits long. The Feature Code default is the first available Feature Code from the Business Communications Manager server (usually 900).

When Call Detail Recording is connected to the unit, a default Feature Code is requested from the Business Communications Manager server. View or modify the Feature Code from the Call Detail Recording Report Parameters window.

To assign or change the Feature Code:

1. Click the **Report Parameters** key.
   The Report Parameters window opens.
2. In the **Feature Code** list box, enter any number between 00 and 99. The first digit (9) is provided.

The appropriate Account Code is now available to all users making billable calls.

Account Code list

Account Codes create a reference for tracking telephone calls. For example, a user contacting a billable client enters an assigned code each time a call is placed to that client.

Account codes consist of a Feature Code (F9--) and an account number. The account number can have a maximum of 12 digits but cannot contain symbols such as (*) or (#). Table 3 gives an example of an Account Code list. Refer to “Sample Account Codes” on page 26.

Table 3 Sample Account Codes

Account code	Description
11127	Pat
37	Field Support
239	Liza
45	Roger
1552	Monique
53	Modern Ways Limited
100	Long distance

Note: Remember to provide your colleagues with the Call Detail Recording Feature Codes and the Account Code list.

Using Account Codes

You can associate Account Codes with any incoming or outgoing calls. To assign an Account Code from any Business Communications Manager telephone, enter the Feature Code (F9--) followed by the account number.

You can enter an Account Code any time during a call. However, you cannot enter the Account Code when a call is on hold or when a configuration session is in progress.

The Report Options

When you click on the Report options key in the Comprehensive window (see Figure 1), the window shown in Figure 5 appears. Refer to "The Report Options window" on page 27.

Figure 5 The Report Options window



Table 4 shows the parameters you can configure using the Report options window. Refer to "Report Options parameters" on page 27.

Table 4 Report Options parameters

Date Format	MM/DD/YY	DD/MM/YY	YY/MM/DD	
Header Format	Line/Station	Source/ Destination		
DNIS Info	Disable	Enable		
Connect Char	Disable	Enable		
Clip File Schedule	Daily	Weekly	Monthly	File size
File size (100KB)	14 (1,400 KB)			
Disk Space Limit	400 (MB)			

Caution: Some of the above parameters are market specific. If the parameter value does not match the trunk property, Call Detail Recording can produce incorrect reports. If you are using a Call Accounting package to process reports, consult your software vendor before you make any changes. File size is used only when this option is selected in the Clip File Schedule.

Date Format

The Date Format includes the day, month and year. There are three date formats. Select one of the following:

- MM/DD/YY
- DD/MM/YY
- YY/MM/DD

The default Date Format is MM/DD/YY. This parameter affects only the Norstar Record Format. It is intended to provide market compatibility.

To assign or change the Date Format:

1. Click the **Report Options** key.
   The Report Options window opens.
2. In the **Date Format** list box, select **MM/DD/YY**, **DD/MM/YY** or **YY/MM/DD**.

Header Format

There are two kinds of Header Format. Select one of the following:

- Line/Station
- Source/Destination

The Header Format default is Line/Destination. This parameter applies to the Norstar Record Format only.

The Line/Station format always reports the line number followed by the station number. The Source/Destination format always reports the number placing the call followed by the number receiving the call. Incoming calls are reported in the Line/Station format. Outgoing calls are reported in the Station/Line format.

To assign or change the Header Format:

1. Click the **Report Options** key.
   The Report Options window opens.
2. In the **Header Format** list box, select **Line/Station** or **Source/Destination**.

DNIS Info

The Dialed Number Identification Service (DNIS) provides the number the caller dialed to reach the Business Communications Manager system.

You can enable or disable the DNIS Info parameter. The DNIS Info default is Enabled. This parameter applies to the Norstar Record Format only. Not all trunks support DNIS.

To enable or disable the DNIS Info options:

1. Click the **Report Options** key.
   The Report Options window opens.
2. In the **DNIS Info** list box, select **Enable** or **Disable**.

Connect Char (Characters)

Normally, Call Detail Recording reports all the digits the user dialed to connect a call. The digits can include digits responding to prompts from an Auto-attendant, extension transfer or voice mail service. To distinguish between digits dialed to connect the call and digits dialed after the call is connected, you can insert an "!" between the two sets of digits.

You can enable or disable the Connect Char parameter. The Connect Char default is Disabled.

To enable or disable the **Connect Char** options:

1. Click the **Report Options** key.
   The Report Options window opens.
2. In the **Connect Char** list box, select **Enable** or **Disable**.

Note: Some of the Report Options parameters are market specific. If the parameter value does not match the trunk property, Call Detail Recording can produce incorrect reports. If you are using a Call Accounting package to process reports, consult your software vendor before you make any changes.

Clip File Schedule

By default, the Business Communications Manager server clips the data files when the file size reaches the maximum of 1,400 kilobytes (KB). You can change the file schedule to clip at regular intervals. The Clip File Schedule options are:

- daily: at midnight
- weekly: Sunday at midnight
- monthly: the first day of each month at midnight
- file size: from 1,000 KB and 5,000 KB
- On File Transfer: when the files are transferred

File size

Data file size limit for clipping is changeable. File size ranges from 10 (1,000 KB) to 50 (5,000 KB).

Note: The File size parameter is not used when a regular interval is assigned, but only when the Clip file Schedule option is selected.

Disk Space limit

The minimum disk space requirement for Call Detail Recording is 2 MB. The default is 400 MB. Available disk space is verified when the service starts and when files are clipped.

When the minimum amount of disk space is available automatic file deletion occurs, beginning with the oldest file. Files are deleted until 20% space is made available. For example, if the disk size is assigned as 400 MB, Call Detail Recording deletes old files until 320 MB of space is available.

The Market Parameters

There are seven Market Parameters. The seven Market Parameters are:

- CLID with Name
- Long CLID Support
- CLID with Call Type
- Support Call Charge
- Answer Supervision
- Call Filter Duration
- Hospitality Record

Click on the Market parameters key in the Comprehensive window (Figure 1) to open the window as shown in Figure 6. Refer to "The Market Parameters window" on page 30.

Figure 6 The Market Parameters window



Table 5 shows the parameters you can configure using the Market Parameters window. Refer to "The Market Parameters window parameters" on page 30.

Table 5 The Market Parameters window parameters

CLID with Name	Long CLID Support	CLID with Call Type	Support Call Charge	Answer Supervision	Call Filter Duration	Hospitality Record
Disable	Disable	Disable	Disable	Disable	0-30 Sec.	Disable
Enable	Enable	Enable	Enable	Enable		Enable

Caution: Some of the Report Options parameters are market specific. If the parameter value does not match the trunk property, Call Detail Recording can produce incorrect reports. Changing the Market Parameters can affect some Access Bin Settings or Suppress Length Settings parameters. If you are using a Call Accounting package to process reports, consult your software vendor before you make any changes.

CLID with Name

Call Detail Recording reports the CLID name of each call. You can enabled or disabled this parameter at any time. The CLID with Name default setting is Enabled. This parameter applies to the Norstar Record Format only. Not all trunks support Name CLID.

Long CLID Support

Call Detail Recording supports long CLID digit reporting. The Long CLID Support default setting is Disabled. This parameter is market specific. Do not change the default unless the trunk supports this feature.

CLID with Call Type

Call Detail Recording supports long distance or unknown call types. The CLID with Call Type default setting is Enabled. This parameter applies to the Norstar Record Format only. Do not change the default unless the trunk supports this feature.

Support Call Charge

Call Detail Recording supports charges on calls. The Support Call Charge default setting is Disabled. This parameter is market specific. Do not change the default unless the trunk supports this feature.

Answer Supervision

Call Detail Recording identifies the telephone number answering outgoing calls. The Answer Supervision default setting is Disabled. This parameter is market specific. Do not change the default unless the trunk supports this feature.

Call Filter Duration

Call Detail Recording reports the length of all outgoing call connections. The Call Filter Duration default setting is 2 seconds. The duration range is zero to 30 seconds.

Hospitality Record

Call Detail Recording represents four states of room occupancy: vacant, basic, mid and full. Room number lengths range from one to five digits.

Assign or Change Market Parameters

To assign or change the Market Parameters:

1. Click the **Market Parameters** key.
   The Market Parameters window opens.
2. From the **CLID With Name** list box, select **Enable** or **Disable**.
3. From the **Long CLID Support** list box, select **Enable** or **Disable**.

4 From the **CLID With Call Type** list box, select **Enable** or **Disable**.

5 From the **Support Call Charge** list box, select **Enable** or **Disable**.

6 From the **Answer Supervision** list box, select **Enable** or **Disable**.

7 In the **Call Filter Duration** box, enter a number between 0 and 30.

8 In the **Hospitality Record** box, select **Enable** or **Disable**.

The Prefix Bin Settings

Click on the Prefix Bin Settings key in the Comprehensive window (see Figure 1) to open the window as shown in Figure 7. Refer to "The Prefix Bin Settings window" on page 32.

Figure 7 The Prefix Bin Settings window



Prefix filter

If you select the Prefix filter, you must also specify the prefix digits. The Prefix option allows you to monitor and report all long distance calls, calls to certain area codes or calls to specific numbers.

If the first digits dialed match one or more of the programmable prefix strings, the call is reported, otherwise the call is not reported. You can have a maximum of eight prefix strings assigned at one time. The maximum length for each prefix string is eight digits. The Prefix filter default settings are 0, 1, 90, 91, 411 and 9411.

Assign or Change Prefix Bin Settings

To assign or change a Prefix filter:

1. Click the **Prefix Bin Settings** key.
   The Prefix Bin Settings window opens.
2. In the **Prefix 1** list box, enter the prefix number.
3. In the **Prefix 2** through **Prefix 8** list boxes, enter the prefix numbers as required.

The Access Bin Settings

Click on the Access Bin Settings key in the Comprehensive window, (see Figure 1) to open the window as shown in Figure 8. Refer to "The Access Bin Settings and Suppress Length Settings window" on page 33.

Figure 8 The Access Bin Settings and Suppress Length Settings window



Use the Access Bin Settings window to configure parameters for Access Bin Settings 1 to 5 and Suppress Length Settings 1 to 5.

Access Bin Settings

Access Bin Settings codes are used to access certain long distance carriers. Personal Identification Numbers (PIN) can be associated with these codes. The long distance user dials the code of the carrier (up to five digits) followed by the PIN (0 to 16 digits), followed by the telephone number to make long distance calls. Access Bin Settings provide security to the long distance user by suppressing the printing of the PIN in the output reports.

Suppress Length Settings

You can have a maximum of five codes assigned at any one time. Each code is a maximum of five digits and can be associated with a suppression number equal to the length of the PIN. The first digits dialed are compared to the Access Bin Settings. If there is a match, the next digits are suppressed. The number of digits suppressed equals the value in the suppress field for that code. Only the Access Bin Settings numbers and the remaining digits (excluding the PIN) are printed in the output report.

Assign or Change Access Bin Settings and Suppress Length Settings

To enter or change the Access Bin Settings:

1 Click the **Access Bin Settings** key.
The Access Bin Settings Suppress Length Settings window opens.

2 In the **Access 1** list box, enter the access code.

3 In the **Access 2** through **Access 5** list boxes, enter the access code as required.

To enter or change the Suppress Length Settings:

4 In the **Suppress 1** list box, enter the Suppression Setting.

5 In the **Suppress 2** through **Suppress 5** list boxes, enter the Suppression Setting as required.

Note: You can suppress a maximum of 16 digits following the Access Bin Settings.

Saving configuration changes

The Call Detail Recording Administration feature of Unified Manager enables you to maintain a copy of all options and parameters. When you complete the configurations and changes required to all parameters, follow the procedures below to save and implement them. Changes do not apply until you select the Commit option or reboot the system. When you click on Configuration in the menu bar, the Configuration reminder window shown in Figure 9 appears. Refer to “The Configuration reminder window” on page 35.

Figure 9 The Configuration reminder window



The Configuration reminder window updates automatically as changes are made to other parameters. Changes do not go into effect until Commit or Undo are assigned.

Table 6 shows the parameter you can configure using the Configuration reminder window. Refer to"Configuration reminder window" on page 35.

Table 6 Configuration reminder window

Changes to Status and Startup are immediate	Other changes exist requiring Commit or Undo
Yes	Yes
	No

Note: In the Configuration Reminder window the 'Changes to Status and Startup are immediate' and 'Other changes exist requiring Commit or Undo' parameters are read-only fields.

The Configuration menu

The Configuration menu is available from all of the Call Detail Recording Administration window. The three options under Configuration are: Commit, Undo and Clip File. Figures 10, 11, and 12 show the three Configuration option windows.

Configuration Commit

Call Detail Recording Administration maintains a copy of all options and parameters internally. Changes made are not applied until the Commit option is selected or the system reboots. Make the changes required to all parameters. When changes are complete, select Commit to apply the changes. Refer to "The Commit option window" on page 36.

Figure 10 The Commit option window



Commit changes

To make and apply changes:

1. From the **Business Communications Manager** key, click the **Services** key.
2. Click the **Call Detail Recording** key or any key in the **Call Detail Recording** submenu.
3. From the **Configuration** menu, choose **Commit**.

The Unified Manager applies changes to the parameters and generates a new header in the Call Detail Recording log file.

Note: Before you commit a change, the ‘Other changes exist requiring Commit or Undo’ parameter appears as Yes in the Configuration Reminder window. When you commit the change, the parameter automatically changes to No.

Configuration Undo

Call Detail Recording Administration maintains a copy of all options and parameters internally. Undo restores the settings to the last committed values. Refer to “The Undo option window” on page 37.

Figure 11 The Undo option window



Undo changes

To undo changes and restore previous values:

1. From the **Business Communications Manager** key, click the **Services** key.
2. Click the **Call Detail Recording** key or any key in the **Call Detail Recording** submenu.
3. From the **Configuration** menu, choose **Undo**.

Previously committed values are restored.

Note: Before you commit a change, the ‘Other changes exist requiring Commit or Undo’ parameter appears as Yes in the Configuration Reminder window. When you commit the change, the parameter automatically changes to No.

Configuration Clip File

The current file log is not accessible when Call Detail Recording Service is running. Call Detail Recording Administration closes the current log file and creates a new log file with a new header. Refer to “The Clip File option window” on page 38.

Figure 12 The Clip File option window



Clip File

To clip the file log:

1. From the **Business Communications Manager** key, click the **Services** key.
2. Click the **Call Detail Recording** folder or any key in the **Call Detail Recording** submenu.
3. From the **Configuration** menu, choose **Clip File**.

The format for the data file extension created is YYYYMMDDHHMMSS. You can download these files using the Unified Manager.

1. Click the **Call Detail Recording** key.
2. From the **Tools** menu, choose **Web Download**.
3. From the Call Detail Recording section, click the log file.
4. Save the log file to the designated directory.

Data File Transfer

The Data File Transfer feature provides you with a method of sending the Call Detail Recording files to a central server.

A typical application of the Data File Transfer feature is when a company with several branch offices wants to analyze the telephony traffic at its branch offices using the Call Detail Recording information. Without the Data File Transfer feature, someone at the central office has to access each branch office individually and down load the files before the analysis can be done. Using the Data File Transfer feature, the Call Detail Recording information is automatically transferred from all of the branch offices to a central server on a defined schedule.

Features of Data File Transfer

- You can schedule a data file transfer so that the Business Communications Manager system sends the data files on a regular basis (daily, weekly or monthly) and at a specified time.
- You can manually start the transfer of data files from the Business Communications Manager system when you need the Call Detail Recording information immediately.
- Business Communications Manager can compress the Call Detail Recording information to reduce the amount of time it takes to transfer the files.
- Business Communications Manager can automatically attempt to re-send the data if the initial data transfer fails.
- Only the files that have not been sent before are transferred.

Central server requirements

The server you are transferring the Call Detail Recording information to must have the following:

- an FTP Server application installed
- a ZIP/UNZIP utility installed
- a username/password defined for use by the Business Communications Manager system that has the appropriate access for FTP transfer
- the FTP Server application is configured to receive connections from the desired Business Communications Manager systems
- write permissions are granted to the appropriate directories for putting the files transferred from the Business Communications Manager system

Scheduling the transfer of the Call Detail Recording information

You can schedule a Data File Transfer to occur on a regular basis. When you create the schedule, you need to specify:

- where the files are transferred to
- how often the transfer should occur
- on which day the transfer starts
- at what time the transfer starts

To schedule a transfer of the Call Detail Recording information:

1. Start Unified Manager.
2. Click the **Services** key and then click the **Call Detail Recording** key.
3. Click the **Data File Transfer** heading.
   The Data File Transfer screen appears.
4. Configure the Data File Transfer parameter according to Table 7.

Table 7 Data File Transfer parameters

Setting	Description
Transfer Type	Allows you to select how often the Call Detail Recording information is sent to a central server. **Push-Daily** – The information is sent once a day at the time entered in the Transfer Time box. **Push-Weekly** – The information is sent once a week at the time entered in the Transfer Time box and the day entered in the Day of Week box. **Push-Monthly** – The information is sent once a month at the time entered in the Transfer Time box and the date entered in the Day of Month box. **None** – The files are not sent to a central server. The default for this parameter is **None**.
IP Address or Machine Name	Allows you to enter the IP address or Machine name of the central server to which you are sending the Call Detail Recording information. An IP address must be entered in the proper dotted format (for example, 10.10.10.1.) A machine name can be up to 47 characters long.
Remote User	Allows you to enter the FTP login user name that Business Communications Manager uses when connecting to the central server. The Remote User name must be the same as the user name you assigned to Business Communications Manager in the central server configuration. The Remote User name can be up to 47 characters. If you leave the **Remote User** box blank, the Business Communications Manager system uses the userid “anonymous” with no password to access the FTP server. **Note**: If you use the “anonymous” userid, there is no security provided for the Call Detail Recording files on the FTP server. Anyone who logs on to the FTP server with the “anonymous” userid can access your Call Detail Recording information.
Remote Password	Allows you to enter the FTP login password that Business Communications Manager uses when connecting to the central server. The Remote Password must be the same as the password you assigned to Business Communications Manager in the central server configuration. The Remote Password can be up to 47 characters.
Destination FTP Alias	Allows you to specify an FTP alias on the central server where the Call Detail Recording information is transferred. An example of a Destination FTP Alias is: **\Telephone_systems\Call_Records**. In the central server configuration, you must grant FTP writing permission on this location for the user name you entered in the Remote User box and the password you entered in the Remote Password box. The Destination FTP Alias can be up to 47 character. **Note**: If you leave the **Destination FTP Alias** box blank, the Call Detail Recording files are transferred to the ftp home directory for that particular userid.

Table 7 Data File Transfer parameters

Setting	Description
Number of Retries	Allows you to specify the number of times that Business Communications Manager attempts to send the Call Detail Recording information to the central server when a data file transfer fails. Enter a value from 0 to 10 as the Number of Retries. If you enter a value of 0, Business Communications Manager does not attempt to send the data again. The default for this parameter is 0.
Delete file after Transfer	Allows you to specify if the Call Detail Recording data files are deleted from the Business Communications Manager after the files are successfully transferred to the central server. Select **Yes** to delete the files after they are successfully sent. Select **No** to leave the files on the Business Communications Manager system. The default for this parameter is No.
Compress File before Transfer	Allows you to specify if the Call Detail Recording data files are compressed into one ZIP file before they are transferred to the central server. The name of the zip file created is *BCM machine name*+ *year* (4 digits)+ *month* (2digits)+ *day* (2digits)+ *hour* (2 digits)+ *minute* (2digits)+ *second* (2 digits)+ *.zip*. For example: SouthBCM20010915084522.zip. Select **Yes** to compress the files into a single ZIP file. Select **No** to send the files uncompressed. The default for this parameter is Yes.
Transfer Time	Allows you to specify the time of day when the Call Detail Recording files are transferred to the central server. Enter the time in hours and minutes according to the 24 hour clock (00:00 to 23:59). The default for this parameter is 00:00 (midnight). **Note**: The Transfer Time is based on the local time of the Business Communications Manager, not on the time at central server.
	Only one of the following three fields appears on the screen.
Transfer Day	This field appears when you select **Push-Daily** as the Transfer Type. This is a read only field that always displays Daily.
Day of Week	This field appears when you select **Push-Weekly** as the Transfer Type. Allows you to specify the day of the week when the transfer will occur. You can select Monday, Tuesday, Wednesday, Thursday, Friday, Saturday or Sunday. The default for this parameter is Monday.
Day of Month	This field appears when you select **Push-Monthly** as the Transfer Type. Allows you to enter the day of the month when the transfer will occur. You can enter a value from 1 to 31. The default for this parameter is 1. **Note**: If you enter 29, 30 or 31 for the Day of Month, the Call Detail Recording files will not be sent on some months. This occurs because some months do not contain these dates. For example, the month of February never has 30 or 31 days. If you want the files sent at the end of every month, use the default values for Transfer Time (00:00) and Day of Month (1).
Last Transfer Time	Displays the last time the Call Detail Recording data files were successfully sent to the central server.

Note: If you are transferring Call Detail Recording files from several Business Communications Manager systems to a single central server, Nortel Networks recommends that you stagger the time of the transfers so that the central server is not overloaded with too many requests.

Transferring the Call Detail Recording information immediately

When you transfer immediately, the Business Communications Manager system uses the information entered on the Data File Transfer screen, but sends the Call Detail Recording information immediately.

To transfer the Call Detail Recording information immediately:

1. Start Unified Manager.
2. Click the **Services** key and then click the **Call Detail Recording** key.
3. Click the **Data File Transfer** heading.
   The Data File Transfer screen appears.
4. Set the parameters on the Data File Transfer screen to specify the server to which the Call Detail Recording information is sent.
   For information about the parameters on this screen, refer to Table 7 on page 40.

Note: When using the Transfer Immediately option, the following fields are not used and can be ignored: **Transfer Type**, **Transfer Time**, **Transfer Day**, **Day of Week** and **Day of Month**.

5. On the **Configuration** menu, click **Transfer immediately**.
   The Business Communications Manager starts transferring Call Detail Recording information to the specified server.

Chapter 3
Call Detail Recording Reports

SL-1 reports

Use the SL-1 report when the you are supplying the output to legacy commercial accounting package or equipment. SL-1 reports are in the form of one or two lines in ASCII characters.

This section describes the SL-1 reports and explains how to interpret them.

Report logs

Report logs reside in the Business Communications Manager Call Detail Recording LOG directory. Use logs for call accounting processing and call activity review.

To download report logs:

1. From the Unified Manager login window, enter the user ID and password.
2. From the **Tools** menu, select **Web Download**.
3. From the Call Detail Recording section, click the log file.
4. Save the log file to the designated directory.

SL-1 report types

The Call Detail Recording supports two different SL-1 report types:

- SL-1 Standard report
- SL-1 CLID report

The SL-1 CLID format is similar to the SL-1 Standard format with the addition of CLID information. For lines that do not support CLID or when the Business Communications Manager server does not deliver CLID information, calls report in an SL-1 Standard report format.

SL-1 report field definitions

Table 7 and Table 8 show summaries of field definitions for SL-1 reports, line 1 and line 2. Refer to "Field definitions for line 1" on page 44 and "Field definitions for line 2" on page 44.

Table 8 Field definitions for line 1

Column	Name	Format	Definition
1	RecType	Y	report type
2	Blank		Blank space
3-5	RecNo	XXX	report seq number
6	Blank		Blank space
7-8	CustNo	00	Customer number
9	Blank		Blank space
10-16	OrigID	TXXXXXX	Line number
		DNXXXX	STN number
		CF00001	Conference number
17	Blank		Blank space
18-24	TerID	TXXXXXX	Line number
		DNXXXX	STN number
25-37	Blank		Blank space
38-48	TimeStamp	MM/DD HH:MM	Time stamp
49	Blank		Blank space
50-57	Duration	HH:MM:SS	Call duration
58	Blank		Blank space
59-90	Digits	XXX...X	Dialed digits
50-61	AccCode	XXX...X	Account code (C report)

Table 9 Field definitions for line 2

Column	Name	Format	Definition
3-18	CLID	XXX...X	CLID number
11-15	AOCE	XXXXXX.XX	Call charges
11-15	Pulse Charge	nnnnn (00000-32767)	Pulse charge for the call. Valid only for ETSI ISDN lines which support AOCE.
17-22	Currency Charge	nnnnn (000000-999999)	Currency charge for the call. Valid only for DASS2 and ETSI ISDN lines which support AOCE.

SL-1 report options

Call Detail Recording generates the SL-1 report options using letter codes, as shown in Table 9. Refer to "Report options and letter codes" on page 45.

Table 10 Report options and letter codes

Letter code	Report option
I	Initialization report
N	Normal report
S	Start report
E	End report
A	Authorization report
C	Charge report
M	Conference Charge report

The I (Initialization) report option contains only the report type and time stamp. The S (Start) option, E (End) option, M (Conference charge) option, and C (Charge) option reports do not contain the duration field. The E (End) option report does not contain any dialed digits.

Note: The I report does not contain Call Information number; all other report types contain the Call Information number (if delivered).

SL-1 Standard reports

Figure 13 shows an example of an outgoing call on line 52 from station set 7425. Refer to "Sample outgoing call" on page 45.

Figure 13 Sample outgoing call

```
N 027 00 DN7425  T052000            04/04 14:03 00:01:32 5551212
```

Figure 14 shows an example of an incoming call on line 47 to station set 2221. Refer to "Sample incoming call" on page 45.

Figure 14 Sample incoming call

```
N 028 00 T047000 DN2221             04/04 14:22 00:12:04
```

Figure 15 shows an example of an outgoing call on line 38 from station set 7447 and transferred to station set 2221. Refer to "Sample call transfer" on page 46.

Figure 15 Sample call transfer

```
S 029 00 DN7447  T038000            04/04 15:02          8761344
E 030 00 T038000 DN2221             04/04 15:07
```

Figure 16 shows an example of a two-line conference call with two outgoing calls. Refer to "Sample conference call" on page 46.

Figure 16 Sample conference call

```
S 000 01 DN6545  T038000            04/04 12:23          9369552
E 001 01 CF0001  T038000            04/04 12:27
S 002 01 DN6789  T047000            04/04 12:23          8082635
E 003 01 CF0001  T047000            04/04 12:27
```

SL-1 CLID reports

The SL-1 CLID report consists of two lines. The CLID information, if available, appears in the third character position of the second line.

The CLID number is always 16 digits. Any missing numbers are represented by an "x." If there is no CLID Information available then no CLID Information report is delivered.

Figure 17 shows an example of an incoming call on line 38 to station set 2221 with CLID enabled. The CLID number available is 4037692000. Refer to "Sample incoming call with CLID" on page 46.

Figure 17 Sample incoming call with CLID

```
N 034 00 T038000 DN2221             04/04 15:32 00:10:24
  4037692000xxxxxx
```

Figure 18 shows an example of an incoming call on line 37 to station set 2211 with Call Information enabled, and the CLID number is not available. Refer to "Sample incoming call with Call Information and without CLID" on page 46.

Figure 18 Sample incoming call with Call Information and without CLID

```
N 035 00 T037000 DN2211             04/04 14:22 00:12:04
```

Figure 19 shows an example of an incoming call on line 38 to station set 7447 and transferred to station set 2223. Call Information is enabled, and the Call Information number available is 4032919001. Refer to "Sample incoming call transferred with Call Information available" on page 46.

Figure 19 Sample incoming call transferred with Call Information available

```
S 029 00 T038000 DN7447             04/04 15:02
  4032919001xxxxxx
E 030 00 T038000 DN2223             04/04 15:07
  4032919001xxxxxx
```

SL-1 Target line/Physical lines

When target lines are used on digital trunks, reports show both the target line number and the physical line number.

Figure 20 shows an example of an incoming call on target line 103 and transferred to another station set. The physical line is 37. Refer to “Sample target line transfer” on page 47.

Figure 20 Sample target line transfer

```
S 029 00 T037103 DN7499              04/04  15:02
E 030 00 T037103 DN7370              04/04  15:07
```

Auto Attendant and Call Center station set numbers

When the Auto Attendant answers incoming calls, the station set number reports as the DN of the Auto Attendant. When Call Center answers incoming calls, the station set number reports as the Control DN (CDN) of the Skillset that answered the call.

Advice of charges at end of call (AOCE)

On ISDN ETSI lines only, the cost of a call is available on an SL -1 record. Cost appears in dollars or pulse units. The maximum amount chargeable to an SL-1 account is $999999 or 99999 units.

Figure 21 shows an example of end of call with currency charges of $123.45. The amount is rounded down to the nearest dollar. Refer to “Sample end of call with charges rounded down” on page 47.

Figure 21 Sample end of call with charges rounded down

```
N 003 00 DN0285   T181000            07/19  16:43  00:00:02 999
          00000  000123
```

Figure 22 shows an example of end of call with currency charges of $123.50. The amount is rounded up to the nearest dollar. Refer to “Sample end of call with charges rounded up” on page 47.

Figure 22 Sample end of call with charges rounded up

```
N 002 00 DN0285   T181000            07/19  17:21  00:00:03 888
          00000  000124
```

Figure 23 shows an example of end of call with pulse charges of 456 units. Refer to “Sample end of call with pulse charges” on page 47.

Figure 23 Sample end of call with pulse charges

```
N 012 00 DN0285   T181000            07/19  17:31  00:00:02 99
          00456  000000
```

Figure 24 shows an example of end of call with zero charges. Refer to "Sample end of call with no charge" on page 48.

Figure 24 Sample end of call with no charge

```
N 013 00 DN0285   T181000           07/19  17:33  00:00:04 45678
          00000  000000
```

Figure 25 shows an example of end of call with charges not available. Refer to "Sample end of call with charges not available" on page 48.

Figure 25 Sample end of call with charges not available

```
N 001 00 DN0285   T181000           07/19  17:43  00:00:02 888
```

Norstar reports

Use Norstar reports when the you assign the Business Communications Manager Call Detail Recording output to a printer or Call Accounting package designed to use the Norstar report.

This section describes the Norstar report and explains how to interpret the reports.

Norstar report types

The Call Detail Recording supports four different Norstar report types:

- Standard report
- CLID report
- Real Time report
- All report

Norstar Standard reports

Norstar Standard reports always start with a header line indicating the date (MM/DD/YY) time (HH/MM/SS), LINE field and STN field. The reports have at least one event line showing an event and time stamp.

Figure 26 sows an example of an Outgoing call in Standard format. Refer to "Sample outgoing call" on page 48.

Figure 26 Sample outgoing call

```
--------   04/04/99   11:39:43   LINE = 0003   STN = 7425
00:00:00   OUTGOING CALL
           DIGITS DIALED    5551212
00:00:37   ACCOUNT CODE     87
00:12:59   CALL RELEASED
```

Figure 27 shows an example of an Incoming Call in Standard format. Refer to "Sample incoming call" on page 49.

Figure 27 Sample incoming call

```
--------   04/04/99   12:00:01   LINE = 0083   STN = 7726
00:00:00   INCOMING CALL    RINGING 0:32
00:00:39   HOLD
00:01:12   UNHOLD
00:02:47   CALL RELEASED
```

Norstar CLID reports

When you select this option, CLID information received from the Business Communications Manager server for an incoming call prints between the report header and the event lines. There is one occurrence of CLID information per call. A CLID field does not appear in the report when CLID information is not available.

If you need Secondary CLID information, you must configure the Primary Call Detail Recording to receive CLID information. You must configure The Primary Call Detail Recording to print SL-1 CLID report format or Norstar CLID report format.

Note: Call Detail Recording reports CLID information only for lines that are capable of delivering CLID. You must configure the Business Communications Manager server to enable delivery of CLID information.

Norstar report field definitions

The first Call Information line after the header line is the CALLING NUMBER. It contains a maximum of 11 characters. When information is incomplete, one of the following messages appear:

- If the number is truncated the forward slash symbol '/' precedes the digits received.
- If a partial CLID number is received, 'x' follows the digits received.
- If the number field does not receive data, 'UNKNOWN' appears.

The second Call Information line is the NAME. It contains a maximum of 15 characters.

- If the name field does not receive data, 'UNKNOWN' appears.

The third Call Information line is the call type indicating when the call is a long distance call.

- If the call type field does not receive data, 'UNKNOWN' appears.

Figure 28 shows an example of an incoming call with CLID. Refer to "Sample incoming call with CLID" on page 50.

Figure 28 Sample incoming call with CLID

```
--------   04/04/99   11:12:01   LINE = 0013   STN = 7465
           CALLING NUMBER   4032919123
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
00:00:00   INCOMING CALL    RINGING 0:32
00:00:39   HOLD
00:01:12   UNHOLD
00:02:47   CALL RELEASED
```

Figure 29 shows an example of an abandoned (no answer) incoming call with CLID. Refer to "Sample call with CLID not answered" on page 50.

Figure 29 Sample call with CLID not answered

```
--------   04/04/99   20:30:00   LINE = 0035
           CALLING NUMBER   4032919123
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
00:00:00   NO ANSWER        RINGING 3:15
```

Figure 30 shows an example of a call report with CLID number truncated. Refer to "Sample call with truncated CLID" on page 50.

Figure 30 Sample call with truncated CLID

```
--------   04/04/99   11:12:01   LINE = 0013   STN = 7465
           CALLING NUMBER   /12345678901
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
00:00:00   INCOMING CALL    RINGING 0:32
00:00:39   HOLD
00:01:12   UNHOLD
00:02:47   CALL RELEASED
```

Figure 31 shows an example of a call with only a partial CLID number. Refer to "Sample call with partial CLID" on page 50.

Figure 31 Sample call with partial CLID

```
--------   04/04/99   11:12:01   LINE = 0013   STN = 7465
           CALLING NUMBER   1234567890x
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
00:00:00   INCOMING CALL    RINGING 0:32
00:00:39   HOLD
00:01:12   UNHOLD
00:02:47   CALL RELEASED
```

Norstar Real Time report format

Real Time call records are one line long. All Real Time records begin with an asterisk (*) to differentiate them from non-Real Time call records. Real Time records are generated only when CLID Information is available. Real Time records also generate five call states and four Hospitality types.

Call Detail Recording generates the Norstar Real Time report options using letter codes, as shown in Table 10. Refer to "Report options and letter codes" on page 51.

Table 11 Report options and letter codes

Letter code	Report option
G	Ringing
D	Dialed Number Identification Service (DNIS)
A	Answered
N	No Answer
T	Transfer
R	Released
HV	Hospitality vacant
HB	Hospitality basic
HM	Hospitality mid

The RINGING call state is unique to Real Time records. It indicates a ringing line as soon as Call Detail Recording receives the CLID Information.

The Dialed Number Identification Service (DNIS) record is reported only if the line delivers the DNIS information. If present, it follows the RINGING record.

Figure 32 shows an example of a call, ringing with DNIS, answered and released. Refer to "Sample call with DNIS" on page 51.

Figure 32 Sample call with DNIS

```
*030198 154615 0019           6137635114     John Doe        U G

*030198 154615 0019           6137635114     4037352000      U D

*030198 154623 0019    7832   6137635114     John Doe        U A

*030198 154831 0019    7832   6137635114     John Doe        U R
```

Figure 33 shows an example of a transferred call. Refer to "Sample call transfer" on page 52.

Figure 33 Sample call transfer

```
*041197 094105 0003            7692000        Alan Smith      U G

*041197 094105 0003            7692000        7305432         U D

*041197 094111 0003    7344    7692000        Alan Smith      U A

*041197 094156 0003    7440    7692000        Alan Smith      U T

*041197 094414 0003    7440    7692000        Alan Smith      U R
```

You can use the record information to drive external PC database applications, for example, to compile customer information by extracting the CLID data from the Real Time records.

Norstar All report format

When selected, this report provides Standard, CLID Information and Real Time records.

Figure 34 shows an example of a call record when All is selected. The RINGING records shows the call received time with CLID Information, not the start alert time. The call is answered 15 seconds after the ringing began. It is transferred 25 seconds after it is answered and is released two minutes after it was transferred. Refer to "Sample call with Standard, CLID and Real Time information" on page 52.

Figure 34 Sample call with Standard, CLID and Real Time information

```
*030298 154920 0022            4037692000     UNKNOWN       D G

*030298 154920 0022            4037692000     8002349876    D D

*030298 154935 0022    7101    4037692000     UNKNOWN       D A

*030298 155000 0022    7169    4037692000     UNKNOWN       D T

*030298 155200 0022    7169    4037692000     UNKNOWN       D R

--------   03/02/98   15:49:20   LINE = 0022   STN = 7101
           CALLING NUMBER   4037692000
           NAME             UNKNOWN
           LONG DISTANCE
           DNIS NUMBER      8002349876
           BC = SPEECH
00:00:00   INCOMING CALL    RINGING 0:15
00:00:20   HOLD
00:00:25   TRANSFERRED

--------   03/02/98   15:50:00   LINE = 0022   STN = 7169
00:00:00   FROM TRANSFER
00:00:00   UNHOLD
00:02:00   CALL RELEASED
```

Auto Attendant and Call Center station set numbers

When the Auto Attendant answers incoming calls, the station set number reports as the DN of the Auto Attendant. When Call Center answers incoming calls, the station set number reports as the Control DN (CDN) of the Skillset that answered the call.

Standard Hospitality record format

The Hospitality record represents four states of room occupancy: vacant, basic, mid and full. Room number lengths range from one to five digits.

Figure 35 shows an example of a Standard Hospitality record with room 12345 status set as vacant. Refer to "Sample room status vacant" on page 53.

Figure 35 Sample room status vacant

```
--------   23/01/98   23:49:00   STN = 12345
           HOSPITALITY VACANT
```

Figure 36 shows an example of a Standard Hospitality record with room 732 status set as basic. Refer to "Sample room status basic" on page 53.

Figure 36 Sample room status basic

```
--------   23/01/98   23:49:00   STN = 732
           HOSPITALITY BASIC
```

Figure 37 shows an example of a Standard Hospitality record with room 73 status set to mid. Refer to "Sample room status mid" on page 53.

Figure 37 Sample room status mid

```
--------   23/01/98   23:49:00   STN = 73
           HOSPITALITY MID
```

Figure 38 shows an example of a Standard Hospitality record with room 7 status set to full. Refer to "Sample room status full" on page 53.

Figure 38 Sample room status full

```
--------   23/01/98   23:49:00   STN = 7
           HOSPITALITY FULL
```

Target line/Physical lines

When target lines are used on digital trunks, the Call Detail Recording reports show both the target line and the physical line number.

Figure 39 shows an example of an incoming call on a target line. The target line number is 101 and the physical line number is 38. Station 7466 answers the call. Refer to "Sample target line and physical line" on page 54.

Figure 39 Sample target line and physical line

```
--------   12/12/97   12:00:01   LINE = 0101   STN = 7468
00:00:00   INCOMING CALL
           LINE = 0038
00:28:33   CALL RELEASED
```

Busy reports

Call Detail Recording produces two types of busy reports:

- Direct Inward Dial
- Target Line

Direct Inward Dial (DID) busy

A call rings busy when the digital line is set up as a DID line requiring receive digits to route the call through the Business Communications Manager server via a target line. If all target line destinations are busy, the unit returns a busy signal instead of routing the call to the prime station set. Call Detail Recording produces a busy report. Figure 40 shows an example of a busy call to a set with DID. Refer to "Sample busy call with DID" on page 54.

Figure 40 Sample busy call with DID

```
--------   03/02/99   15:09:32   LINE = 0235
00:00:00   BUSY
           LINE = 0035
```

Target line busy

A call rings busy when a target line is involved with a call, and a second incoming call tries to use the same line. Call Detail Recording produces a busy report, but does not include the target line information. Figure 41 shows an example of a call to a busy target line. Refer to "Sample busy call on a target line" on page 54.

Figure 41 Sample busy call on a target line

```
--------   03/02/99   14:36:02   LINE = 0035
00:00:00   BUSY
```

Call Detail Recording reports busy only if the Business Communications Manager server is programmed to provide busy treatment.

Bearer capability data

When you assign Call Detail Recording to report in the Norstar CLID report format, Call Detail Recording provides Bearer capability information associated with the call. Figure 42 shows an example of an incoming call with Bearer capability data. Refer to "Sample incoming call with Bearer capability" on page 55.

Figure 42 Sample incoming call with Bearer capability

```
--------   12/03/99   14:36:00   LINE = 0035
           CALLING NUMBER   7355303
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
00:00:00   NO ANSWER        RINGING  0:02
```

Note: This information appears in the Norstar report when the Business Communications Manager server supports Bearer capabilities.

PRI Call-by-call service

When the ISDN Primary Rate Interface (PRI) trunk is installed in the Business Communications Manager server, Call Detail Recording provides PRI Call-by-call service information as part of the CLID call records in Norstar CLID format. The record provides both the service type and service ID for incoming and outgoing calls. Figure 43 shows an example of an incoming call using the TIE service with service ID 0 and the corresponding outgoing call using the PUBLIC service. Refer to "Sample PRI" on page 55.

Figure 43 Sample PRI

```
--------   01/01/98   01:38:00   LINE = 0001   STN = 221
           CALLING NUMBER   6135551212
           NAME             UNKNOWN
           UNKNOWN
           DNIS NUMBER      9772210
           BC = SPEECH
           PRI SERVICE      TIE 0
00:00:00   INCOMING CALL    RINGING 0:00
00:01:35   CALL RELEASED

--------   01/01/98   01:38:00   LINE = 0023   STN = 223
           BC = SPEECH
           PRI SERVICE      PUBLIC
00:00:00   OUTGOING CALL
           DIGITS DIALED    9772210
00:01:35   CALL RELEASED
```

Note: Business Communications Manager only supports PRI with the necessary hardware installation and the PRI trunks configuration to deliver PRI call-by-call service information.

Voice over IP calls

Calls, both incoming and outgoing, that use the Voice over IP (VoIP) protocol appear in the CLID report. Figure 44 shows an example of an incoming call using Voice over IP. Refer to “Sample incoming call with VoIP” on page 56.

Figure 44 Sample incoming call with VoIP

```
--------   12/03/99   14:36:00   LINE = 0035
           CALLING NUMBER   7355303
           NAME             UNKNOWN
           UNKNOWN
           BC = SPEECH
           VOIP CALL
00:00:00   NO ANSWER        RINGING  0:02
```

Dialed number identification service

Certain trunk types support the delivery of Dialed Number Identification Service (DNIS). Call Detail Recording supports the reporting of DNIS as part of the CLID call reports. Both the Norstar CLID and Norstar Real Time format support DNIS reporting. Figure 45 shows an example of an incoming call with DNIS information. Refer to “Sample incoming call with DNIS” on page 56.

Figure 45 Sample incoming call with DNIS

```
--------   01/01/99   01:38:00   LINE = 0001   STN = 221
           CALLING NUMBER   6135551212
           NAME             UNKNOWN
           UNKNOWN
           DNIS NUMBER      9772210
           BC = SPEECH
           PRI SERVICE      TIE 0
00:00:00   INCOMING CALL    RINGING 0:00
00:01:35   CALL RELEASED
```

Note: Business Communications Manager only support DNIS with the necessary hardware installation and trunk configuration to deliver DNIS information.

Call connected digit separator

Normally, Call Detail Recording reports all the digits the user dials to connect a call. The digits can include digits responding to prompts from the Automated Attendants, extension transfer, or voice mail service. To identify the digits dialed to connect the call and digits dialed after the call is connected, you can insert an “!” between them. Figure 46 shows an example of an outgoing call with call connected digit separator. Refer to “Sample call with digit separator” on page 57.

Figure 46 Sample call with digit separator

```
--------   01/01/99   01:38:00   LINE = 0023   STN = 223
           BC = SPEECH
00:00:00   OUTGOING CALL
           DIGITS DIALED    9772210!0132
00:01:35   CALL RELEASED
```

Note: Call Detail Recording cannot differentiate between digits required to connect a call and extra digits dialed before the call is connected. Not all units support the delivery of call connected signals so this feature is not be available for all Business Communications Manager servers.

External call forward

External call forward occurs when an extension is configured to externally forward calls in three different situations:

- Call Forward All Calls (CFAC)
- Call Forward Busy (CFB)
- Call Forward No Answer (CFNA)

When an incoming call is unanswered and externally forwarded, Call Detail Recording reports the call as outgoing. The reports provides the:

- incoming line or extension
- outgoing line
- extension responsible for the external call forward
- reason for the external call forward
- digits dialled

Note: For more information, refer to the Installation and Maintenance Guide that came with your system.

Figure 47 shows an example of an Incoming Call on line 0001 being externally forwarded to line 0002. Extension 221 is responsible for the external call forward event. Refer to “Sample external call with external call forward” on page 57.

Figure 47 Sample external call with external call forward

```
--------   12/31/99   11:59:59   LINE = 0001   LINE = 0002
           CALLING NUMBER   4032919123
           BC = SPEECH
           EXT CALL FWD          STN  =  221   REASON  = CFAC
00:00:00   OUTGOING CALL
           DIGITS DIALED   5551212
00:02:47   CALL RELEASED
```

Figure 48 shows an example of an internal call being externally forwarded to line 0002. Extension 222 originated the call. Extension 221 is responsible for the external call forward event. Refer to "Sample internal call with external call forward" on page 58.

Figure 48 Sample internal call with external call forward

```
--------   12/31/99   11:59:59   STN  =  222   LINE = 0002
           CALLING NUMBER   4032919123
           BC = SPEECH
           EXT CALL FWD          STN  =  221   REASON  = CFAC
00:00:00   OUTGOING CALL
           DIGITS DIALED   5551212
00:02:47   CALL RELEASED
```

Norstar report field definitions

Figure 49 shows all of the lines available for printing by Call Detail Recording in the Norstar report. Refer to "Standard and CLID report formats" on page 59.

Figure 49 Standard and CLID report formats

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890

--------   MM/DD/YY   HH:MM:SS   LINE = XXXX   STN = XXXXXXX
--------   MM/DD/YY   HH:MM:SS   LINE = XXXX   LINE = XXXX
--------   MM/DD/YY   HH:MM:SS   LINE = XXXX
--------   MM/DD/DY   HH:MM:SS
           RECORD RESTART
00:00:00   INCOMING CALL     RINGING 0:00
00:00:00   OUTGOING CALL
00:00:00   NO ANSWER         RINGING 0:00
00:00:00   FROM TRANSFER
00:00:00   INVALID PASSWORD
00:00:00   HOLD
00:00:00   UNHOLD
00:00:00   ACCOUNT CODE      123
00:00:00   BUSY
           DIGITS DIALED     9369552
00:00:00   CONFERENCE        STN2 = 7425
00:00:00   CONFERENCE        LINE2 = 0052
00:00:00   CONFERENCE END
00:00:00   RESTRICTI0N PASSWORD 99
00:00:00 CALL CHARGES = PULSES
00:00:00   CALL RELEASED
00:00:00   TRANSFERRED
00:00:00   FROM TRANSFER
           RECORDS LOST
           LINE = 0015
           BC = SPEECH
           BC = UNRESTRICTED DIGITAL
           BC = RESTRICTED DIGITAL
           BC = 3.1 kHZ AUDIO
           BC = 7 kHZ AUDIO
           BC = VIDEO
           CALLING NUMBER    4032919123
           CALLING NUMBER    /12345678901
           CALLING NUMBER    4032919123x
           NAME              Peter Pan
           LONG DISTANCE
           UNKNOWN
           DNIS NUMBER       4032652300
           PRI SERVICE       PUBLIC
           PRI SERVICE       PRIVATE
           PRI SERVICE       TIE
           PRI SERVICE       FX
           PRI SERVICE       OUTWATS
           PRI SERVICE       SWITCHED DIGITAL
           PRI SERVICE       INWATS
           PRI SERVICE       INTL INWATS
           PRI SERVICE       900
           HOSPITALITY VACANT
           HOSPITALITY BASIC
           HOSPITALITY MID
           HOSPITALITY FULL
           EXT CALL FWD           STN  =  4221  REASON  = CFAC
           EXT CALL FWD           STN  =  4222  REASON  = CFB
           EXT CALL FWD           STN  =  4227  REASON  = CFNA
           VOIP CALL
```

Figure 50 shows an example of the lines available for printing by Call Detail Recording in the Real Time report. Refer to “Real Time record format” on page 60.

Figure 50 Real Time record format

```
0        1         2         3         4         5         6         7
12345678901234567890123456789012345678901234567890123456789012345678901234567890
*MMDDYY HHMMSS LINE  STATION   CLID NUMBER      NAME/DNIS    TYPE EVENT
*030193 154615 0019            6137635122       Alan Smith      U G
*030193 154615 0019            6137635122       4032632300      U D
*030193 154615 0019    7343    6137635122       Alan Smith      U A
*030193 154615 0019    7343    6137635114       Alan Smith      U N
*030193 154615 0019    7343    6137635122       Alan Smith      U T
*030193 154615 0019    7343    6137635114       Alan Smith      U R
*012398 234900         12345                                    H V
*012398 234900         12345                                    H B
*012398 234900         12345                                    H M
*012398 234900         12345                                    H F
```

Norstar Standard and CLID report description

For non-Real time Standard and CLID reports, each line has a maximum of three fields (except for the header line).

The header line has a maximum of five fields:

- The first field always contains eight dashes.
- The second field provides the date the call originated.
- The third field provides the time the call originated.
- The fourth field provides the line being used.
- The fifth field provides the line, or station using the line, from the fourth field.

Call Detail Recording reports calls based on events (change of call states).

- The first field is the time the associated event occurred. The time is an offset from the start time of the call indicated in the header.
- The second field describes the event associated with that call. Events can be either a call state like hold or transfer, or a user action like account code entry.
- The third field is data that further describes the action indicated in the second field.

Printable line descriptions

Figure 51 shows an example of a header line indicating the start of a call report, or the continuation of a call report after a transfer. This report can have three, four or five fields. The date and time reflect the date and time the call started. For incoming calls, this is when the call is answered. For outgoing calls it is the time the line is seized. The LINE field is fixed at four digits. The STN directory number (DN) ranges from two to seven digits in length. For Outgoing tandem calls, both the fourth and the fifth field are LINE. Refer to “Sample start header line” on page 60.

Figure 51 Sample start header line

```
--------   MM/DD/YY   HH:MM:SS   LINE = XXXX   STN = XXXXXX
```

Figure 52 shows an example of the line following the header line when Call Detail Recording or the Business Communications Manager server re-starts. Refer to “Sample restart line” on page 61.

Figure 52 Sample restart line

```
                    RECORD RESTART
```

Figure 53 shows an example of the line following the header line (with all five fields), or after the CLID Information. The time in the header line shows when the call is answered. This time minus the ringing duration (the third field) shows when the call starts ringing. Refer to "Sample call ringing line" on page 61.

Figure 53 Sample call ringing line

```
          00:00:00   INCOMING CALL    RINGING 0:04
```

Figure 54 shows an example of the line following the header line (with all five fields). The time in the header line field shows when the call is initiated. Refer to "Sample outgoing line" on page 61.

Figure 54 Sample outgoing line

```
          00:00:00   OUTGOING CALL
```

Figure 55 shows an example of the line following the header line when an incoming call is unanswered. Refer to "Sample unanswered call line" on page 61.

Figure 55 Sample unanswered call line

```
          00:00:00   NO ANSWER        RINGING 0:22
```

Figure 56 shows an example of the line indicating when an incoming call receives busy treatment. Refer to "Sample busy line" on page 61.

Figure 56 Sample busy line

```
          00:00:00   BUSY
```

Figure 57 shows an example of the line indicating when the call is put on hold or taken off hold. Refer to "Sample hold and off hold lines" on page 61.

Figure 57 Sample hold and off hold lines

```
          00:00:04   HOLD
          00:00:06   UNHOLD
```

Figure 58 shows an example of the line indicating the start and the end of a conference. The third party in the conference can be a second station set or a second line as indicated in the third field. Refer to "Sample conference start and end lines" on page 61.

Figure 58 Sample conference start and end lines

```
          00:10:32   CONFERENCE       STN2 = 7425
          00:12:12   CONFERENCE       LINE2 = 0052
          00:12:45   CONFERENCE END
```

Figure 59 shows an example of the line indicating when a call is transferred. Refer to “Sample call transfer line” on page 62.

Figure 59 Sample call transfer line

```
00:00:00   TRANSFERRED
```

Figure 60 shows an example of the line indicating when a call was transferred. It indicates the start of the call at the new station set that received the transfer. Refer to “Sample call transfer from line” on page 62.

Figure 60 Sample call transfer from line

```
00:00:00   FROM TRANSFER
```

Figure 61 shows an example of the line indicating the last state of a call. It is followed by a carriage return and two line feeds so that there is a blank line before the start of the next call report. Refer to “Sample end call line” on page 62.

Figure 61 Sample end call line

```
00:00:00   CALL RELEASED
```

Figure 62 shows an example of the line indicating digits dialed appear in Outgoing call reports. A maximum of 32 digits/characters can appear. If the call connected digit separator option is enabled, an “!” appears between digits dialed before and after the call connects. Refer to “Sample digits dialed line” on page 62.

Figure 62 Sample digits dialed line

```
                DIGITS DIALED   XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX
                DIGITS DIALED   123456789!1234
```

Figure 63 shows an example of the line indicating when the user or caller enters an invalid password. Refer to “Sample invalid password line” on page 62.

Figure 63 Sample invalid password line

```
00:00:00   INVALID PASSWORD
```

Figure 64 shows an example of the line indicating when an account code is entered. Account codes can be a maximum of 12 digits. Refer to “Sample account code line” on page 62.

Figure 64 Sample account code line

```
00:00:00   ACCOUNT CODE     XXXXXXXXXXXX
```

Figure 65 is an example of the line indicating when a password is entered. The password ID is a maximum of two digits (00-99). The report indicates the password override ID and not the password itself. Refer to “Sample password” on page 63.

Figure 65 Sample password

```
00:00:00   RESTRICTION PASSWORD XX
```

Figure 66 shows an example of the line indicating the last line of a call report if the call states are missed or if a call is missed altogether. It is followed by a carriage return and two line feeds so that there is a blank line before the start of the next call report. Refer to "Sample last line" on page 63.

Figure 66 Sample last line

```
REPORTS LOST
```

Figure 67 shows and example of the line identifying the physical line of an incoming call on a target line. The line number is fixed at four digits (with leading zeros). Refer to "Sample physical line" on page 63.

Figure 67 Sample physical line

```
LINE = XXXX
```

Figure 68 shows an example of the lines indicating when CLID information is available. The calling number shown can be a maximum of 12 characters of which a maximum of eleven can be digits. If a number received by the Business Communications Manager server is longer than eleven digits, then a "/" is the first character, followed by the eleven least significant digits. The name can be a maximum of 15 characters. Each of the number and name can show "UNKNOWN". The third line is the call type. It shows either "LONG DISTANCE" or "UNKNOWN" if call type information is not available. The DNIS number, if available, appears after the call type. It is followed by the Bearer Capability. The last line is the PRI Call-by-call service which appears only when the PRI service information is available. Refer to "Sample CLID information" on page 63.

Figure 68 Sample CLID information

```
CALLING NUMBER   XXXXXXXXXXX
NAME             XXXXXXXXXXXXXXX
UNKNOWN
DNIS NUMBER      XXXXXXXXXX
BC = SPEECH
PRI SERVICE      TIE XXXXX
VOIP CALL
```

Figure 69 shows an example of the lines indicating when the room occupancy status of room 12345 changes to vacant. Refer to "Sample room status" on page 63.

Figure 69 Sample room status

```
--------   23/01/98   23:49:00   STN = 12345
           HOSPITALITY VACANT
```

Figure 70 shows an example of the line indicating when a call is externally forwarded. Extension 221 is responsible for the external call forward event. Refer to "Sample external call forward" on page 64.

Figure 70 Sample external call forward

```
                    EXT CALL FWD          STN  =  221   REASON  = CFAC
```

Norstar Real Time record description

The Real Time record is one line long beginning with an asterisk (*) to differentiate it from other Norstar records. This record contains eight fields:

- date in MMDDYY format
- time in HHMMSS format
- line number associated with the call
- station set number associated with the call
- CLID number
- CLID name or DNIS number
- call type
- call state

The date field is a fixed length of six digits (MMDDYY). The month, day or year are preceded by a leading 0 to keep the field length fixed. For example, 010501 is January 5, 2001.

The time field is a fixed length of six digits (HHMMSS). There are no separators between hour, minute and second.

The line field shows the call being tracked. The line is fixed at four digits and can have leading zeros. For example, 0019 is line 19. As the Real Time Hospitality record does not use the third field it does not contain any characters and appears blank.

The station set number field shows the station set associated with the call. Station set numbers range from two to seven digits. If the number is less than seven digits there are no leading zeros because this field is not fixed. In the Real Time Hospitality record this field shows the room number. Room numbers range from one to five digits.

The CLID Information field shows the calling number. The number is a maximum of 12 characters (11 digits maximum and the “/” and “x” character). There is always information in this field. If no number is available, either UNKNOWN or PRIVATE appears in this field. As the Real Time Hospitality record does not use this field it appears blank.

The CLID name or DNIS information field shows the name. The name is a maximum of 15 characters. If no name is available, UNKNOWN appears in this field. DNIS information in “D” records replace this field. The DNIS is a maximum of 10 digits. In the Real Time Hospitality record this field shows the room occupancy status indicator.

The CLID call type field shows either long distance (D) or unknown (U) status.

The call state field of the Real Time record always contains a call state indicator, and is followed immediately by a carriage return and two line feeds.

Real Time Hospitality record format

The Real Time Hospitality record represents four states of room occupancy:

- vacant
- basic
- mid
- full

Room number lengths range from one to five digits.

Figure 71 shows an example of a Real Time Hospitality record with room 12345 status set to vacant. Refer to "Sample room status vacant" on page 65.

Figure 71 Sample room status vacant

```
*012398 234900        12345                                H V
```

Figure 72 shows an example of a Real Time Hospitality record showing room 732 status set to basic. Refer to "Sample room status basic" on page 65.

Figure 72 Sample room status basic

```
*012398 234900        732                                  H B
```

Figure 73 shows an example of a Real Time Hospitality record showing room 73 status set to mid. Refer to "Sample room status mid" on page 65.

Figure 73 Sample room status mid

```
*012398 234900        73                                   H M
```

Figure 74 shows an example of a Real Time Hospitality record showing room 7 status set to full appears below. Refer to "Sample room status full" on page 65.

Figure 74 Sample room status full

```
*012398 234900        7                                    H F
```

Advice of charges at end of call

On ISDN ETSI lines only, the cost of a call is available on a Norstar record. Cost appears in dollars or pulse units.

Figure 75 shows an example of end of call currency charges of $123.45. Refer to "Sample charges in dollars" on page 66.

Figure 75 Sample charges in dollars

```
--------   07/19/00   16:13:11   LINE = 0181   LINE = 285
           BC = SPEECH
00:00:00   OUTGOING CALL
           DIGITS DIALED   54672
           CALL CHARGE = 123.45 $
00:00:08   CALL RELEASED
```

Figure 76 shows an example of end of call currency charges of 123 Lira. Refer to "Sample charges in lira" on page 66.

Figure 76 Sample charges in lira

```
--------   07/19/00   16:16:56   LINE = 0181   LINE = 285
           BC = SPEECH
00:00:00   OUTGOING CALL
           DIGITS DIALED   98
           CALL CHARGE = 123 Lira
00:00:03   CALL RELEASED
```

Figure 77 shows an example of end of call pulse charges of 456 units. Refer to "Sample charges in units" on page 66.

Figure 77 Sample charges in units

```
--------   07/19/00   16:28:15   LINE = 0181   LINE = 285
           BC = SPEECH
00:00:00   OUTGOING CALL
           DIGITS DIALED   546
           CALL CHARGE = 456 PULSES
00:00:04   CALL RELEASED
```

Figure 87 shows an example of end of call with no charges. Refer to "Sample with no charges" on page 66.

Figure 78 Sample with no charges

```
--------   07/19/00   16:29:40   LINE = 0181   LINE = 285
           BC = SPEECH
00:00:00   OUTGOING CALL
           DIGITS DIALED   55
           CALL CHARGE = 0
00:00:03   CALL RELEASED
```

Figure 79 shows an example of end of call with charges not available. Refer to "Sample charges not available" on page 66.

Figure 79 Sample charges not available

```
--------   07/19/00   16:26:13   LINE = 0181   LINE = 285
           BC = SPEECH
00:00:00   OUTGOING CALL
00:00:02   CALL RELEASED
           00:00:02   CALL RELEASED
```

Chapter 4
Install CDRClient Application

The CDRClient application allows you to administer remotely the domain and user access to the Call Detail Recording records. You can view and print records. You also control record security.

To install the CDRClient application:

1. Exit any Windows® programs that are running.
2. Disable any anti-virus programs that are running.
3. On the Unified Manager front page, click the **Install Clients** button.
   The Client Install Application page appears.
4. Click the **Call Detail Recording** link.
   The Call Detail Recording page appears.
5. Click the **Download Call Detail Recording Server** button.
   A file download window appears.
6. Select **Save this program to disk** and click the **OK** button.
   The SaveAs dialog appears.
7. Choose a location to save this file to and click the **Save** button.
   The file begins downloading.
8. When the file is finished downloading, click the **Close** button.
9. Double-click the **EEClient.exe** file.
10. Follow the instructions on the display to complete the installation.
11. When completed, CDRClient appears under the **Start** menu.

Call Detail Recording display

CDRClient allows you to monitor records remotely as calls occur. To access CDRClient:

1. Click the **Start** button, point to **Programs.**
2. Point to and click **CDRClient**.
   The CDRClient window appears.

The CDRClient window

Using CDRClient you can view and print records. Figure 80 shows an example of the CDRClient window. Refer to “CDRClient window” on page 68.

Figure 80 CDRClient window



To use CDRClient:

1 Type the server name to connect to the Business Communications Manager server.

2 Click the **Set Server** button to apply the name.

3 Click the **Start** button to view call activity records.

Note: If you do not know the server name, ask your System Administrator.

The CDRClient maintains a limited number of records. New records replace old records after the buffer is full.

4 Click the **Stop** button to stop viewing call activity records.

To print records as you view them:

1 Select the record you want to print or right click on the mouse to Select All.

2 Click the **COPY** button or right click on the mouse to copy the record to the clipboard.

3 Paste the record into a text application such as WordPad or Notepad.

4 Print the record.

Note: All records are maintained on the Business Communications Manager server. Use Business Communications Manager Unified Manager to obtain records and print files.

Call Detail Recording Record Security

The records from Call Detail Recording are sensitive in nature. Communication among top executives and external companies, telephone banking passwords, long distant PIN codes, etc. are some of the examples that require protection from unauthorized access. With the introduction of network real time access in Call Detail Recording, the System Administrator must setup the system to protect against unauthorized access.

The default installation of Call Detail Recording enables the CDR group to have launch permission to the records. This means anyone in the same group has access to the Call Detail Recording records.

To guard against unauthorized access to Call Detail Recording records, you must add only the authorized users to the Call Detail Recording group. In this configuration, the NT security protects all records against unauthorized access.

CDR Group User Administration

User groups are created during installation. The System Administrator can add user names to the CDR group and grant them access to Call Detail Recording records using the Business Communications Manager Unified Manager. The System Administrator can also modify user access privileges or delete existing user names from the group. Figure 81 shows an example of the User Administration window. Refer to "User Administration window" on page 69.

Figure 81 User Administration window



Note: For more information, refer to the *Programming Operations Guide* that came with your system.

CDR User Management

Under User Management you can:

- create a new user profile
- modify user privileges
- delete a user name

Create a user profile

To add a user name:

1. From the **Business Communications Manager** key, click the **Management** key.
2. Click the **UserManager** key.
3. From the **Configuration** menu, choose **Add User**.
   The Property Sheet window appears. Refer to "Property Sheet window" on page 70.

Figure 82 Property Sheet window



4. Enter the user name and assign privileges to read only. Click **Save**.

The user now has access to Call Detail Recording records.

Modify user privileges

To modify privileges a user can access:

1. From the **Business Communications Manager** key, click the **Management** key.
2. Click the **UserManager** key.

3 Click on the user name.

4 From the **Configuration** menu, choose **Modify User**.
The Property Sheet window appears.

5 Modify the access privileges. Click **Save**.

The user's privileges are now changed.

Delete a user name

To delete a name from a user list:

1 From the **Business Communications Manager** key, click the **Management** key.

2 Click the **UserManager** key.

3 Click on the user name.

4 From the **Configuration** menu, choose **Delete User**.

The user's name is now deleted from the list.

Call Detail Recording Domain User Management

Under Domain User Management you can:

- add a domain user profile
- modify user privileges
- delete a user name

Add a name to a Domain User Group

To add a name to the Domain User Group Profile:

1 From the **Business Communications Manager** key, click the **Management** key.

2 Click the **UserManager** key.

3 From the **Configuration** menu, choose **Add Domain User**.
The Domain User Group Profile window appears. Refer to "Domain User Group Profile window" on page 72.

Figure 83 Domain User Group Profile window



4 Enter the domain and user name, and assign privileges to read only. Click **Save**.

The user now has access to the Call Detail Recording records.

Modify user privileges

To modify user privileges:

1 From the **Business Communications Manager** key, click the **Management** key.

2 Click the **UserManager** key.

3 Click on the user name.

4 From the **Configuration** menu, choose **Modify Domain User**.
The Property Sheet window appears.

5 Modify the access privileges. Click **Save**.

The user's privileges are now changed.

Delete a user name

To delete a domain user name from the list:

1 From the **Business Communications Manager** key, click the **Management** key.

2 Click the **UserManager** key.

3 Click on the domain and user name.

4 From the **Configuration** menu, choose **Delete Domain User**.

The user's name is now deleted from the list.

CDR User Management additional information

Call Detail Recording Domain User Management, in the previous section, uses a domain server network as an example for the launch permission administration. In addition, the Business Communications Manager server must be registered as a member server of the domain.

The configuration differs for a peer-to-peer network. In this case, the Business Communications Manager server is not registered as a member server in the network. This appears in the CDR Group User Administration, in the previous section.

The group/user accounts must exist in the Business Communications Manager server before the CDR server launches permission administration. The Business Communications Manager server takes responsibility to verify if the users have the right launch permission.

If the remote PC is a Windows NT® workstation, ensure the user accounts in the launch permission list exist on both the server and the client PC with matching passwords. When the user logs in to the remote PC using one of the authorized user accounts, the user has the launch permission to the Business Communications Manager server. The System Administrator can administer local users from Unified Manager by clicking the Management and UserManager keys, and then the Configuration menu.

Note: The domain passwords of the users in the launch permission list must be the same as the passwords in the corresponding Business Communications Manager server user accounts.

The System Administrator is responsible for ensuring the system configuration is secure.

Glossary

This Glossary provides terms used in the Business Communications Manager Call Detail Recording System Administration Guide.

Account feature code

A three-digit number that enables users to enter a Call Detail Recording account code from a two-line display telephone.

Baud

A variable unit of data transmission speed equal to one bit per second.

Business Communications Manager

Call Detail Recording is an application on your Business Communications Manager system used to record call activity.

Business Communications Manager server

The central hardware component in the Business Communications Manager system. This unit has its own processor and memory, and provides a physical point for connection of various types of data terminals, telephones and expansion modules.

Call Accounting

An optional software program used to analyze the data collected by Call Detail Recording and to organize it according to a company’s needs.

Call report

A type of report created by Call Detail Recording. This report includes information about a call's duration and number dialed. Call report information is collected to itemize telephone activity.

CLASS

Custom Local Area Signalling Services is a collection of services from the local telephone company.

CLID

When available from the local telephone company, Calling Line Identification shows the calling number on the telephone display.

CMS

Call Management Services is a collection of services from the local telephone company. CMS is a part of CLASS.

Default

A value that Call Detail Recording assumes unless another one is specified.

External Call Forward

A Business Communications Manager telephone is configured to forward calls to destinations external to the system using outgoing lines.

Hospitality Record

A type of record created by Call Detail Recording that provides the room occupancy status whether vacant, basic, mid or full.

ISDN

Integrated Services Digital Network is a worldwide digital communications network.

Norstar report format

An English language syntax organization of call reports.

Physical line

The physical connection between the Business Communications Manager system and the outside world.

SL-1 report format

The organization of information that Call Detail Recording data must be translated into before the data it contains is read by an SL-1 call accounting program.

System Administrator

The person responsible for installing, administrating and maintaining Call Detail Recording for a particular company.

Target line

A Target line is a virtual line, not a physical line. It is dedicated to receiving and routing incoming calls on DID or auto-answer trunks to a specific destination.

Index

Numbers

911 13

A

Access Bin Settings and Suppress Length Settings
accessing 33
Account Bin Settings 34
acronyms 14
Auto Attendant, station set numbers 47, 53

B

Business Communications Manager Call Detail Recording, about 17
Business Communications Manager Unified Manager 19
Management 19
Resources 19
Services 19, 21
System 19
Busy
Norstar Direct Inward Dial 54
Norstar Reports 54
Norstar Target line 54

C

Call Center station set numbers 47, 53
Call connected 56
Call information 49
Comprehensive
accessing 20
Connect Characters 29
conventions, text 13

D

Date Format 28
Descriptions 60
Norstar Reports 60
Real Time record 64
Dialed number 56
information 28
Digit separator 56
Direct Inward Dial 54

E

Emergency 911 13
External call forward 63

F

Feature Codes 25
creating list 26
using 26
Field definitions 58
CLID report 49
Format
Date 28
Header 28

H

Header Format 28
Hospitality record 17
Real Time 65
Standard 53

I

Identification service 56

K

Keys 21

L

Language
Report 24
Long distance
Prefix filter 25, 32

M

Market Parameters
accessing 30

N

Norstar report 58
Norstar Target line 54

P

Physical lines
Norstar 53
SL-1 47
Prefix Bin Settings
accessing 32
Primary Rate Interface 55
Printable line 60
Programming
Business Communications Manager Call Detail Recording parameters 19
publications
related 15

R

Remote administration 73
Report filter 24
Report format
Norstar 23, 48, 49
Norstar All 52
Norstar Real Time 51
Norstar Standard 48
Norstar, call charges 65
SL-1 23, 43
SL-1 CLID 46
SL-1 field definitions 44
SL-1 Report options 45
SL-1 Standard 45
SL-1, Call charges 47
Report language 24
Report logs 43
Report Options
accessing 27
Report Parameters
accessing 22
Report type
Norstar 48
SL-1 43
Reports
Bearer capability 54
Busy 54
SL-1 43

S

Summary
accessing 20
Suppress Length Settings 34

T

Target lines
SL-1 47
text conventions 13

U

Unified Manager
Diagnostics 19